

View Online at <https://aerobasegroup.com/nsn/6625-00-489-0602>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

1.610 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.320 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.320 inches

**Overall Height:**

1.760 inches

**Overall Width:**

1.760 inches

**Mounting Stud Length:**

0.530 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Nut 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+0.050 to 15.000 kilohertz

**Dial Scale Marking Color:**

Black and red single indicator 1st range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

0.820 inches

**Meter Body Diameter Behind Mounting Flange:**

1.320 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Yellow single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

-20.0 to 3.0 voice units single indicator 1st range

**Mounting Stud Diameter:**

0.112 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Cadmium

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0