NSN 6625-00-489-6409

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-489-6409

view Offilite at https://aerobasegroup.com/histi/0025-00-405-0405
Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.850 inches
Mounting Hole Diameter:
Between 0.143 inches and 0.157 inches
Overall Diameter:
3.510 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Mtg hdw 3; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+360.000 to 440.000 hertz
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.5 to 2.5 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.660 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range

External

NSN 6625-00-489-6409

Voltmeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0 to 500.0 volts, af single indicator single range
Features Provided:
Zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Operating Voltage Rating In Volts:
Between 120.0 ac and 225.0 ac
Special Features:
Ruggedized
Special Markings:
Red line at 120, 208, 240 and 416 volts
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304/13
Style Designator:
Round flush mtg
Supplementary Features:
Within the ranges of 115 to 125 volts and 200 to 250 volts the percent of error shall not be more than 5 volts and 10 volts respectively
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0