

View Online at <https://aerobasegroup.com/nsn/6625-00-489-6412>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

1.938 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

25 single indicator single range

**Frequency Rating:**

400.0 hertz

**Overall Diameter:**

2.625 inches

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and vibration resistant

**Mounting Bolt Circle Diameter:**

2.440 inches

**Furnished Items And Quantity:**

Term. Hdw 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.125 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 125.0 kilowatts single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Phase:**

Three

**Special Features:**

Ruggedized

**Special Markings:**

Red line at 100

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-m-10304 style 36

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0