

View Online at <https://aerobasegroup.com/nsn/6625-00-491-0967>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.812 inches

Mounting Stud Length:

0.406 inches

Overall Diameter:

2.312 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Distance Between Mounting Facility Centers:

1.656 inches

Furnished Items And Quantity:

Nut 4; lockwasher 4; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

300.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.875 inches

Meter Body Diameter Behind Mounting Flange:

2.093 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0 to 300.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.125 inches

Scale Selection Method:

Terminal

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized; sealed

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0