NSN 6625-00-491-5581

Wattmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-491-5581

View Online at https://aerobasegroup.com/nsn/6625-00-491-5581
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.469 inches
Mounting Hole Diameter:
Between 0.143 inches and 0.157 inches
Overall Diameter:
3.500 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Term. Hdw 2; mtg hdw3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.188 inches
Meter Body Diameter Behind Mounting Flange:
2.812 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range

Power Source:

External

NSN 6625-00-491-5581

Wattmeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0 to 250.0 watts single indicator single range
Features Provided:
Luminous scale marking and magnetic shield and zero adjuster
Criticality Code Justification:
Feat
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Critical application: communications and data systems; poseidon material (hull, mech, elec, ord and elect.)
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304, type mr36w100dcuar
Style Designator:
Round flush mtg
Supplementary Features:
Internal resistance 1250 ohms; ruggedized
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0