NSN 6625-00-494-0820

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-494-0820

| Circuit Current For Which Designed: |
|---|
| Ac |
| Overall Length: |
| 1.725 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Mounting Stud Length: |
| 0.375 inches |
| Overall Diameter: |
| 2.695 inches |
| Mounting Bolt Circle Diameter: |
| 2.220 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.495 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.205 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 3 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+5.0 amperes, ac single indicator single range |
| Mounting Stud Diameter: |
| 0.125 inches |
| |
| Movement Suspension Method: |

NSN 6625-00-494-0820

Ammeter - Page 2 of 2



| Circuit Attachment Method And Quantity: |
|---|
| 2 solder lug |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set electronic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fila: |

A310a0