

View Online at <https://aerobasegroup.com/nsn/6625-00-494-7077>

Circuit Current For Which Designed:

Ac and dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.843 inches

Mounting Hole Diameter:

0.119 inches

Scale Division Quantity:

50 single indicator 2nd range

Overall Diameter:

3.687 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.093 inches

Furnished Items And Quantity:

Clip 1; nut 3; lockwasher 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

4.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.343 inches

Meter Body Diameter Behind Mounting Flange:

2.125 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+2.0 amperes, ac single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Criticality Code Justification:

Feat

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

6 solder lug

Special Features:

Critical application

Special Markings:

On back, sealed do not open

Material:

Steel

Nuclear Hardness Critical Feature:

Hardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Supplementary Features:

Ruggedized

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0