

View Online at <https://aerobasegroup.com/nsn/6625-00-494-8415>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.437 inches

**Scale Division Quantity:**

20 single indicator single range

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

1.781 inches

**Environmental Protection:**

Watertight

**Furnished Items And Quantity:**

O ring 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Black and green and red single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.781 inches

**Meter Body Diameter Behind Mounting Flange:**

1.469 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

20; 15; 10; 5; 0; colored bands

**Mounting Facility Type And Quantity:**

1 ring and 1 threaded body

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Self-illumination facility and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 solder stud

**Phase:**

Single

**Special Features:**

28 v lamp

**Special Markings:**

Red band from 8 to 12; green band from 0 to 8

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Two term. For lamp

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0