

View Online at <https://aerobasegroup.com/nsn/6625-00-494-8415>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.437 inches

Scale Division Quantity:

20 single indicator single range

Frequency Rating:

60.0 hertz

Overall Diameter:

1.781 inches

Environmental Protection:

Watertight

Furnished Items And Quantity:

O ring 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black and green and red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.781 inches

Meter Body Diameter Behind Mounting Flange:

1.469 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

20; 15; 10; 5; 0; colored bands

Mounting Facility Type And Quantity:

1 ring and 1 threaded body

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 solder stud

Phase:

Single

Special Features:

28 v lamp

Special Markings:

Red band from 8 to 12; green band from 0 to 8

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Two term. For lamp

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0