

View Online at <https://aerobasegroup.com/nsn/6625-00-494-8569>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

5000.0

Overall Length:

2.010 inches

Overall Height:

3.750 inches

Overall Width:

3.750 inches

Scale Division Quantity:

20 single indicator single range

Mounting Stud Length:

0.500 inches

Mounting Bolt Circle Diameter:

3.156 inches

Furnished Items And Quantity:

Term, hdw 2; mtg hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.907 inches

Meter Body Diameter Behind Mounting Flange:

2.805 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Percent voltage; m 20; m 10; 0; 10; 20

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

690 ohms resistance

Special Markings:

Low at minus 20, high at plus 20 percent voltage

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0