

View Online at <https://aerobasegroup.com/nsn/6625-00-494-8569>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

5000.0

**Overall Length:**

2.010 inches

**Overall Height:**

3.750 inches

**Overall Width:**

3.750 inches

**Scale Division Quantity:**

20 single indicator single range

**Mounting Stud Length:**

0.500 inches

**Mounting Bolt Circle Diameter:**

3.156 inches

**Furnished Items And Quantity:**

Term, hdw 2; mtg hdw 3

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.907 inches

**Meter Body Diameter Behind Mounting Flange:**

2.805 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Percent voltage; m 20; m 10; 0; 10; 20

**Mounting Facility Type And Quantity:**

3 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Mounting Stud Diameter:**

0.138 inches

**Features Provided:**

Zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

690 ohms resistance

**Special Markings:**

Low at minus 20, high at plus 20 percent voltage

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0