

View Online at <https://aerobasegroup.com/nsn/6625-00-495-2286>

Circuit Current For Which Designed:

Dc

Overall Length:

1.437 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.260 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.260 inches

Overall Height:

1.646 inches

Overall Width:

1.646 inches

Scale Division Quantity:

4 single indicator 1st range

Mounting Stud Length:

0.394 inches

Furnished Items And Quantity:

Mtg nuts 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

215.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

0.870 inches

Meter Body Diameter Behind Mounting Flange:

1.480 inches

Background Color:

Gray, light single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

Upper scale: 0 in center; pos and neg signs; lower scale: m 10; m 6; m 3; m 2; m 1; 0; 1; 2; 3; indicates voice units

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator 2nd range

Mounting Stud Diameter:

0.086 inches

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 solderless lug

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0