

View Online at <https://aerobasegroup.com/nsn/6625-00-495-2286>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.437 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.260 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.260 inches

**Overall Height:**

1.646 inches

**Overall Width:**

1.646 inches

**Scale Division Quantity:**

4 single indicator 1st range

**Mounting Stud Length:**

0.394 inches

**Furnished Items And Quantity:**

Mtg nuts 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

215.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

0.870 inches

**Meter Body Diameter Behind Mounting Flange:**

1.480 inches

**Background Color:**

Gray, light single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Scale Marking:**

Upper scale: 0 in center; pos and neg signs; lower scale: m 10; m 6; m 3; m 2; m 1; 0; 1; 2; 3; indicates voice units

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator 2nd range

**Mounting Stud Diameter:**

0.086 inches

**Features Provided:**

Zero adjuster

**Circuit Attachment Method And Quantity:**

2 solderless lug

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0