NSN 6625-00-498-4344

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-498-4344

| Circuit Current For Which Designed: |
|---|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 1800.0 |
| Overall Length: |
| 3.000 inches |
| Overall Height: |
| 0.920 inches |
| Overall Width: |
| 2.258 inches |
| Scale Division Quantity: |
| 20 single indicator single range |
| Environmental Protection: |
| Dust tight and humidity resistant and shock resistant and vibration resistant |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 1 clamp |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+10.0 amperes, dc single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Ruggedized |

NSN 6625-00-498-4344

Ammeter - Page 2 of 2



| Material: |
|---|
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Special Test Features: |
| Complies with ansi specification c-39.1 |
| Style Designator: |
| Rectangular surface mtg |
| Fsc Application Data: |
| Test set electronic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A310a0