

View Online at <https://aerobasegroup.com/nsn/6625-00-500-0824>

Overall Length:

20.313 inches

Overall Height:

12.500 inches

Overall Width:

10.000 inches

Current Type:

Ac

Frequency Rating:

Between 0.050 kilohertz and 1.000 kilohertz

Accessory Components And Quantity:

1 case, 2 prod test, 2 cable assemblies, 1 mtg bracket

Voltage Rating:

Between 103.8 volts and 126.5 volts

Beam Quantity:

1

Mounting Method:

Chassis

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Any acceptable

Sweep Frequency Range:

+80.0/+200000.0 hertz

Single Trigger Sweep Duration:

Between 1.2 seconds and 120000.0 seconds

Trigger Sweep Voltage Amplitude Rating:

5.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

10 usec intervals at 2000 yds and 50 used intervals at 10000 yds

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Frequency Response Rating:

Provided

Y-axis Frequency Response Rating:

Between 50.0 hertz and 5000000.0 hertz

Z-axis Frequency Response Rating:

Between 50.0 hertz and 5000000.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Special Features:

Esecond y-axis frequency response rating is 10.0 cps min. And 8.0 mcps max; second z-axis freq response is 10.0 cps min and 8.0 mcps max; y-axis impedance 1met porm 5 pct shunted w/26 uuf porm 2 uuf

Reference Number Differentiating Characteristics:

W/spares

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-g