NSN 6625-00-504-0370

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-504-0370

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

2.406 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

3.468 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.968 inches

Furnished Items And Quantity:

Nut 6; lockwasher 6

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range and red single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.156 inches

Meter Body Diameter Behind Mounting Flange:

2.718 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Scale reads, r. F. Monitor

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

NSN 6625-00-504-0370 Special Scale Meter - Page 2 of 2



So	cale Graduation Type:
No	onlinear single indicator single range
Fe	eatures Provided:
Ze	ero adjuster
M	ovement Suspension Method:
Je	wel pivot base
Ci	rcuit Attachment Method And Quantity:
21	threaded stud
Sp	pecial Features:
Rı	uggedized
Sp	pecial Markings:
Oı	n back, sealed do not open; on front, r.F. Monitor adjust to red line
M	aterial:
St	eel
N	uclear Hardness Critical Feature:
No	pnhardened
Sı	urface Treatment:
Pa	aint
Sp	pecial Test Features:
С	omplies with mil-m-10304
St	yle Designator:
Ro	bund flush mtg
Fs	c Application Data:
Τe	est set, elect. Equip.
Sł	nelf Life:
N/	a
Uı	nit Of Measure:
De	emilitarization:
No	
Fi	ig:
A3	310a0