

View Online at <https://aerobasegroup.com/nsn/6625-00-504-0372>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

2.485 inches

**Mounting Hole Diameter:**

0.150 inches

**Scale Division Quantity:**

50 single indicator single range

**Overall Diameter:**

4.564 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Mounting Bolt Circle Diameter:**

4.137 inches

**Furnished Items And Quantity:**

Nut 10; lockwasher 8

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Six hole/stud bolt circle

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.375 inches

**Meter Body Diameter Behind Mounting Flange:**

3.636 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

0; 20; 40; 60; 80; 100; transmission

**Mounting Facility Type And Quantity:**

6 screw and 6 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

On back, sealed do not open; on front, transmission

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Cadmium

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0