NSN 6625-00-504-2279

Arbitrary Scale Meter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-504-2279

Mounting Hole Diameter: 0.150 inches Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 2.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 2.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Overall Diameter: 3.500 inches Mounting Bolt Circle Diameter: 2.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Mounting Bolt Circle Diameter: 2.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Mounting Bolt Circle Diameter: 2.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
2.160 inches Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Panel Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Mounting Arrangement Style: Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Three hole/stud bolt circle Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Dial Scale Marking Color: Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Black single indicator single range Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Meter Depth Behind Mounting Flange: Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Between 0.751 inches and 1.250 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
3 unthreaded hole Circuit Attachment Method And Quantity: 2 solder stud
Circuit Attachment Method And Quantity: 2 solder stud
2 solder stud
0
Special Markings:
Red line at center scale, marked set to red line and output
Style Designator:
Round flush mtg
Reference Number Differentiating Characteristics:
As differentiated by the circuit current for which designed requirement, special markings requirement and circuit attachment method
requirement
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A310a0