

View Online at <https://aerobasegroup.com/nsn/6625-00-504-2488>

Width:

15.500 inches

Length:

15.600 inches

Ac Voltage Rating:

Between 105.0 volts and 125.0 volts

Frequency Rating:

Between 50.0 hertz and 800.0 hertz

Major Components:

Adapter; test set, radar; waveguide, flexible; cable assembly, power, assy; cable assembly, rf; cable assembly, video; horn, pickup

Accessory Component Quantity:

1 and 1 and 1 and 2 and 1 and 1 and 2 and 1

Accessory Controlling Agency:

Jcens

Internal Battery Accommodation:

Not included

Test Type For Which Designed:

Power and frequency measurements of radar transmitter; alignment of radar receivers; observation of rf and video pulses

Operating Test Capability:

Frequency measurements, range 8500 to 10500 mc; power measurements, p5 to p30 dbm over frequency range; signal generator, range, 8500 to 10500 mc, output power, m5 to m100 dbm, internal modulation, pulse 0.25 to 10 usec, internal modulation, fm 0 to 5 mc/sec cw, external modulation, pulse 0.2 to 10 usec; synchroscope, deflection sensitivity, 0.5 v/sec, band with, 8 mc, low frequency response, 3 db down at 1000 cps, sweep duration 5, 20, 250.4000 usec; gated spectrum analyzer, tuning range 8500 to 10500 mc, sensitivity, m55 dbm, resolution to 50 kc

Phase:

Single

Height:

16.400 inches

Departure From Cited Document:

N/a

Departure From Cited Designator:

N/a

Reference Number Differentiating Characteristics:

Per sperry gyroscope co, dwg no. 620279

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T228-a