

View Online at <https://aerobasegroup.com/nsn/6625-00-504-2502>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.828 inches

Scale Division Quantity:

5 single indicator single range

Overall Diameter:

2.281 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 2; lockwasher 2; copper gasket 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

10.0 microamperes

Dial Scale Marking Color:

Black single indicator single range and red single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.140 inches

Meter Body Diameter Behind Mounting Flange:

2.046 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Percent explosive; 0; 20; 40; 60; 80; 100; m-s-a; explosimeter

Mounting Facility Type And Quantity:

1 bezel

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

M-5-a; explosimeter

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate and paint

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0