## NSN 6625-00-504-2603

Ammeter - Page 1 of 2

Ac

Overall Length: 11.000 inches

3.375 inches

3.375 inches

Overall Height:

**Circuit Current For Which Designed:** 

Between 4.250 inches and 4.750 inches



View Online at https://aerobasegroup.com/nsn/6625-00-504-2603

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Center To Center Distance Between Mounting Facilities Parallel To Width:

| Overall Width:  |
|---|
| Between 4.250 inches and 4.750 inches                 |
| Scale Division Quantity:                              |
| 50 single indicator single range                      |
| Mounting Stud Length:                                 |
| Between 0.500 inches and 0.750 inches                 |
| Environmental Protection:                             |
| Dustproof   |
| Indicator Type:                                       |
| Dial w/pointer  |
| Installation Design:                                  |
| Panel   |
| Mounting Arrangement Style:                           |
| Four hole/stud rectangular/square                     |
| Frequency Response Range:                             |
| +392.000/+408.000 hertz                               |
| Dial Scale Marking Color:                             |
| Black single indicator single range                   |
| Accuracy In Percent:                                  |
| -1.5/+1.5 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange:                   |
| 10.000 inches   |
| Meter Body Diameter Behind Mounting Flange:           |
| 3.980 inches  |
| Movement Type:  |
| Moving iron vane                                      |
| Background Color:                                     |
| White single indicator single range                   |
| Pointer Color:  |
| Black single indicator single range                   |
| Power Source:   |
| External  |

## NSN 6625-00-504-2603

Ammeter - Page 2 of 2



| Mounting Facility Type And Quantity:   |
|--|
| 4 threaded stud  |
| Scale Graduation Type:   |
| Linear single indicator single range   |
| Measurement Range:   |
| +0.0/+100.0 amperes, ac single indicator single range  |
| Mounting Stud Diameter:  |
| 0.250 inches   |
| Scale Selection Method:  |
| Switch   |
| Features Provided:   |
| Zero adjuster  |
| Movement Suspension Method:  |
| Jewel pivot base   |
| Circuit Attachment Method And Quantity:  |
| 2 threaded stud  |
| Material:  |
| Steel  |
| Nuclear Hardness Critical Feature:   |
| Nonhardened  |
| Style Designator:  |
| Rectangular flush mtg  |
| Test Data Document:  |
| 81349-mil-m-10304/4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A310a0   |
|  |
|  |