

View Online at <https://aerobasegroup.com/nsn/6625-00-519-1954>

**Overall Length:**

15.000 inches

**Overall Height:**

16.938 inches

**Overall Width:**

6.813 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Accessory Components And Quantity:**

1 detector, 1 attenuator, 1 adapter, 1 test prod cathode, 1 cable assembly

**Voltage Rating:**

115.0 volts

**Beam Quantity:**

1

**Mounting Method:**

Portable

**Screen Size:**

3 in.

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Not included

**Single Trigger Sweep Duration:**

Between 10.0 microseconds and 200000.0 microseconds

**Trigger Sweep Voltage Amplitude Rating:**

50.0 volts

**Trigger Sweep Polarity Switch:**

Included

**Trigger Sweep Marker Intervals:**

1, 10, 100, 1000, and 10000 usec

**Expanded Sweep:**

Not provided

**Amplifier Deflection Sensitivity Provision:**

Provided

**Vertical Deflection Sensitivity Voltage Rating:**

100.0 millivolts rms per inch

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Provided

**Direct Connection Vertical Deflection Sensitivity Voltage Rating:**

15.0 volts cw outside diameter and 18.0 volts peak outside diameter

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

Between 5.0 hertz and 20000.0 hertz

**Y-axis Frequency Response Rating:**

Between 10.0 hertz and 4000000.0 hertz

**Z-axis Frequency Response Rating:**

Between 20.0 hertz and 4000000.0 hertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Z-axis Input Impedance Rating:**

1.0 megohms

**Calibrated Screen Scale:**

Not included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T320-g