

View Online at <https://aerobasegroup.com/nsn/6625-00-519-2056>

Mounting Type:

Table

Overall Length:

21.000 inches

Overall Height:

17.125 inches

Overall Width:

17.625 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 100.0 hertz

Case Material:

Aluminum

Case Surface Treatment:

Enameled

Frequency Range Rating:

+1.800/+4.000 gigahertz

Accessory Component Quantity:

1 and 1 and 1 and 2 and 1 and 3

Accessory Controlling Agency:

Jcens; jcens; jcens; jcens; jcens; jcens

Accessory Identifying Number:

Ts-403b/u type no. And cy-669a/u type no. And cx-3277/u/6ft0in type no. And cg-409a/u/8ft2in type no. And cg-92b/u/6ft0in type no. And ug-273/u type no.

Internal Battery Accommodation:

Not included

Output Impedance Rating:

50.0 ohms

Voltage Rating:

Between 103.5 volts and 126.5 volts

Frequency Band Quantity:

1

Modulation Type:

Fm and pulse

Accessory Component Name:

Generator, signal; case; cable assembly, power, electrical; cable assembly, radio frequency; cable assembly, radio frequency; connector, adapter

Calibration Accuracy Rating:

Porm 1.000 percent

Crystal Controlled Feature:

Not provided

Calibrated Signal Output Range:

0.1 uv to 224 mv

Signal Output Constancy:

Form 2 db maximum variation throughout frequency range

Modulator Location:

Internal

Modulated Frequency Rating:

Between 0.050 hertz and 100.0 hertz

Pulse Repetition Frequency Rating:

Between 40.0 hertz and 400.0 hertz

Modulation Degree:

Between 50.0 usec pulse and 125.0 usec pulse

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-j