NSN 6625-00-519-2104



Signal Generator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/6625-00-519-2104 **Mounting Type:** Portable **Overall Length:** 20.625 inches **Overall Height:** 18.500 inches **Overall Width:** 14.938 inches **Current Type:** Ac Frequency Rating: Between 50.0 hertz and 60.0 hertz **Case Material:** Aluminum **Case Surface Treatment:** Enameled Frequency Range Rating: +50.000/+400.000 megahertz **Accessory Component Quantity:** 1 and 1 and 2 and 1 and 1 and 1 and 1 **Accessory Controlling Agency:** Jetds; jetds; jetds; jetds; jetds; measurement corp; measurement corp **Accessory Identifying Number:** Sg-3 type no. And cy-1504/urm-70 type no. And cg-718/u type no. And ug-643/u type no. And ug-564/u type no. And ug-637/u type no. And h-4401 part no. And 4400 part no. **Internal Battery Accommodation:** Not included **Output Impedance Rating:** 50.0 ohms Voltage Rating:

115.0 volts

Frequency Band Quantity:

Modulation Type:

Fm

Accessory Component Name:

Generator, signal; case, signal generator; cable assembly, radio freq; adapter, connector; adapter, connector; adapter, connector; adapter, connector

Calibration Accuracy Rating:

Porm 1.0 pct

Calibrated Signal Output Range:

0.1 to 100, 000 mc calibrated output

Signal Output Constancy:

Porm 2.0 db variation throughout freq range

NSN 6625-00-519-2104 Signal Generator - Page 2 of 2



Modulator Location:
Internal
Modulated Frequency Rating:
Between 1.0 kilohertz and 1.6 kilohertz
Modulation Degree:
0.5 percent
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: T320-j