

View Online at <https://aerobasegroup.com/nsn/6625-00-519-2166>

Circuit Current For Which Designed:

Ac and dc

Overall Length:

2.266 inches

Mounting Hole Diameter:

0.157 inches

Overall Diameter:

Between 3.490 inches and 3.510 inches

Environmental Protection:

Cold resistant and hermetic and heat resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

Between 3.146 inches and 3.174 inches

Furnished Items And Quantity:

Nut 3; shunt res 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.515 inches

Meter Body Diameter Behind Mounting Flange:

2.672 inches

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0 to 150.0 volts, ac single indicator all ranges

Features Provided:

External shunting and rectifier circuit and zero adjuster

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Porm 5 pct res for 0 to 500 dc v range only

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0