

View Online at <https://aerobasegroup.com/nsn/6625-00-519-2888>

**Circuit Current For Which Designed:**

Ac or dc

**Overall Length:**

2.075 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.562 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.250 inches

**Overall Height:**

3.940 inches

**Overall Width:**

4.250 inches

**Mounting Hole Diameter:**

0.141 inches

**Scale Division Quantity:**

60 single indicator 4th range

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Nut 10

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Red single indicator 2nd range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

0.975 inches

**Meter Body Diameter Behind Mounting Flange:**

3.203 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Red single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator 1st range

**Measurement Range:**

+0.0 to 3.0 volts, dc single indicator 4th range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

Vacuum tube voltmeter

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0