NSN 6625-00-521-0481

Voltmeter - Page 1 of 2

Dc

Overall Length:

Circuit Current For Which Designed:

Mounting Facility Type And Quantity:

4 threaded stud



View Online at https://aerobasegroup.com/nsn/6625-00-521-0481

1.330 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.310 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.310 inches
Overall Height:
1.740 inches
Overall Width:
1.740 inches
Scale Division Quantity:
30 single indicator single range
Mounting Stud Length:
0.440 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.000 inches
Meter Body Diameter Behind Mounting Flange:
1.500 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External

NSN 6625-00-521-0481 Voltmeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-15.0 to 15.0 volts single indicator single range
Mounting Stud Diameter:
0.112 inches
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
30 ko res
Special Markings:
+ at pos term.
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Supplementary Features:
Meter to be mounted on a 0.0747 in. Thick panel
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A310a0