

View Online at <https://aerobasegroup.com/nsn/6625-00-521-0481>

Circuit Current For Which Designed:

Dc

Overall Length:

1.330 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.310 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.310 inches

Overall Height:

1.740 inches

Overall Width:

1.740 inches

Scale Division Quantity:

30 single indicator single range

Mounting Stud Length:

0.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.500 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-15.0 to 15.0 volts single indicator single range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

30 ko res

Special Markings:

+ at pos term.

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Meter to be mounted on a 0.0747 in. Thick panel

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0