# NSN 6625-00-528-7964

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-528-7964

## Circuit Current For Which Designed:

Dc

## Dielectric Withstanding Voltage In Volts:

3000.0

## **Overall Length:**

2.380 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

### 2.240 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.240 inches

## **Overall Height:**

3.250 inches

## Overall Width:

3.250 inches

## Scale Division Quantity:

## 25 single indicator single range

Mounting Stud Length:

#### 0.540 inches

#### **Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

#### Furnished Items And Quantity:

Nut 6; lockwasher 6; seal 1

#### Indicator Type:

Dial w/pointer

## Installation Design:

Panel

## Mounting Arrangement Style:

Four hole/stud rectangular/square

## Sensitivity Rating:

5.0 volts

## Dial Scale Marking Color:

Black single indicator single range

## Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

## Unable To Decode:

Unable to decode or unable to decode

## Meter Depth Behind Mounting Flange:

1.060 inches

## Meter Body Diameter Behind Mounting Flange:

2.730 inches

## Movement Type:

Moving coil, permanent magnet

# NSN 6625-00-528-7964

Voltmeter - Page 2 of 2



**Background Color:** White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:** External Mounting Facility Type And Quantity: 4 threaded stud Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0 to 5.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches **Features Provided:** Magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Ruggedized Material: Plastic **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli Fiig: A310a0