

View Online at <https://aerobasegroup.com/nsn/6625-00-534-4929>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.579 inches

**Scale Division Quantity:**

24 single indicator single range

**Overall Diameter:**

1.675 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Furnished Items And Quantity:**

Nut 2; lockwasher 2; seal 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

1000.0 ohms per volt

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.732 inches

**Meter Body Diameter Behind Mounting Flange:**

1.496 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

0; 2; 4; 6; 8; 10; 12

**Mounting Facility Type And Quantity:**

1 threaded body

**Scale Graduation Type:**

Linear single indicator single range

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Meter capaci type 105 volts dc

**Special Markings:**

Percent x10 dc voltage 105

**Material:**

Aluminum alloy

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0