## NSN 6625-00-535-9734

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-535-9734

| Olar Millick Designed                                 |
|---|
| Circuit Current For Which Designed:                   |
|   |
| Dielectric Withstanding Voltage In Volts:             |
| 3000.0  |
| Overall Length:                                       |
| 2.067 inches  |
| Mounting Hole Diameter:<br>0.125 inches               |
|   |
| Scale Division Quantity:                              |
| 25 single indicator single range                      |
| Overall Diameter:                                     |
| 2.695 inches  |
| Mounting Bolt Circle Diameter:                        |
| 2.440 inches  |
| Furnished Items And Quantity:                         |
| Screw 3 no. 4-40, nut 3, washer 3                     |
| Indicator Type:                                       |
| Dial w/pointer Installation Design:                   |
| Panel   |
| Mounting Arrangement Style:                           |
| Three hole/stud bolt circle                           |
| Dial Scale Marking Color:                             |
| White single indicator single range                   |
| Accuracy In Percent:                                  |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange:                   |
| 1.687 inches  |
| Meter Body Diameter Behind Mounting Flange:           |
| 2.210 inches  |
| Movement Type:  |
| Moving coil, permanent magnet                         |
| Background Color:                                     |
| Black single indicator single range                   |
| Pointer Color:  |
| White single indicator single range                   |
| Power Source:   |
| External  |
| Mounting Facility Type And Quantity:                  |
| 3 unthreaded hole                                     |
| Scale Graduation Type:                                |
|   |

Linear single indicator single range

## NSN 6625-00-535-9734

Ammeter - Page 2 of 2



Measurement Range: +0.0/+50.0 microamperes, dc single indicator single range **Features Provided:** Zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 solderless lug Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened Style Designator: Round flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A310a0