NSN 6625-00-538-8828

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-538-8828

view Offilite at https://aerobasegroup.com/hsh/ooz5-00-550-6020
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
2000.0
Overall Length:
2.218 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.875 inches
Overall Height:
2.344 inches
Overall Width:
2.250 inches
Scale Division Quantity:
50 single indicator single range
Environmental Protection:
Dust resistant
Indicator Type:
Dial w/pointer
Installation Design:
Installation Design: Panel
-
Panel
Panel Mounting Arrangement Style:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Panel Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.317 inches
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.317 inches Meter Body Diameter Behind Mounting Flange:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.317 inches Meter Body Diameter Behind Mounting Flange: 2.062 inches
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.317 inches Meter Body Diameter Behind Mounting Flange: 2.062 inches Movement Type:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.317 inches Meter Body Diameter Behind Mounting Flange: 2.062 inches Movement Type: Moving coil, permanent magnet
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.317 inches Meter Body Diameter Behind Mounting Flange: 2.062 inches Movement Type: Moving coil, permanent magnet Background Color:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.317 inches Meter Body Diameter Behind Mounting Flange: 2.062 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range

External

NSN 6625-00-538-8828

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+10.0 milliamperes, dc single indicator single range
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0