

View Online at <https://aerobasegroup.com/nsn/6625-00-538-9047>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1000.0

Overall Length:

2.625 inches

Mounting Hole Diameter:

0.125 inches

Overall Diameter:

2.688 inches

Environmental Protection:

Waterproof

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Mtg hdw 3; term. Hdw 2

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

5

Accuracy In Percent:

-0.3 to 0.3 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.844 inches

Meter Body Diameter Behind Mounting Flange:

2.125 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Reeds have high q characteristics; hermetically sealed; 100 to 130 operating voltage

Material:

Plastic phenol-formaldehyde

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Supplementary Features:

Temperature compensations not required

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0