NSN 6625-00-538-9124

Ammeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-538-9124

Circuit Current For Which Designed:
Dc
Scale Division Quantity:
40 single indicator single range
Overall Diameter:
2.695 inches
Installation Design:
Panel
Sensitivity Rating:
67.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.500 inches
Meter Body Diameter Behind Mounting Flange:
2.187 inches
Background Color:
White single indicator single range
Measurement Range:
Measurement Range: +0.0/+800.0 amperes, dc single indicator single range
-
+0.0/+800.0 amperes, dc single indicator single range
+0.0/+800.0 amperes, dc single indicator single range Features Provided:
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity:
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features:
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings:
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings: Shaded areas above scale arc, green from 0 to 500v, red from 500 to 800v
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings: Shaded areas above scale arc, green from 0 to 500v, red from 500 to 800v Style Designator:
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings: Shaded areas above scale arc, green from 0 to 500v, red from 500 to 800v Style Designator: Round flush mtg
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings: Shaded areas above scale arc, green from 0 to 500v, red from 500 to 800v Style Designator: Round flush mtg Shelf Life:
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings: Shaded areas above scale arc, green from 0 to 500v, red from 500 to 800v Style Designator: Round flush mtg Shelf Life: N/a
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings: Shaded areas above scale arc, green from 0 to 500v, red from 500 to 800v Style Designator: Round flush mtg Shelf Life: N/a
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings: Shaded areas above scale arc, green from 0 to 500v, red from 500 to 800v Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure:
+0.0/+800.0 amperes, dc single indicator single range Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solder stud Special Features: Hermetically sealed Special Markings: Shaded areas above scale arc, green from 0 to 500v, red from 500 to 800v Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: