NSN 6625-00-538-9568

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-538-9568

| Circuit Current For Which Designed: |
|--|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 2000.0 |
| Overall Length: |
| 1.015 inches |
| Scale Division Quantity: |
| 30 single indicator all ranges |
| Overall Diameter: |
| 2.690 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Sensitivity Rating: |
| 54.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 0.890 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.200 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |
| Black single indicator all ranges |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 1 flange |
| Scale Graduation Type: |
| Linear single indicator all ranges |
| Measurement Range: |
| +0.0/+90.0 decibels above or below one watt single indicator 2nd range |
| Scale Selection Method: |
| Torminal |

2 solder stud

Circuit Attachment Method And Quantity:

NSN 6625-00-538-9568

Ammeter - Page 2 of 2

Fiig: A310a0



| Special Markings: |
|---|
| Red line at 20 on low scale and at 60 on high scale |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |