## NSN 6625-00-538-9852

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-538-9852

Circuit Current For Which Designed:
Dc
Overall Length:
4.719 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.750 inches
Overall Height:
4.250 inches
Overall Width:
4.250 inches
Scale Division Quantity:
75 single indicator single range
Mounting Stud Length:
0.500 inches
Furnished Items And Quantity:
Mtg hdw 4; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
T dilet
Mounting Arrangement Style:
Mounting Arrangement Style:
Mounting Arrangement Style: Four hole/stud rectangular/square
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.969 inches
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.969 inches Meter Body Diameter Behind Mounting Flange:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.969 inches Meter Body Diameter Behind Mounting Flange: 3.969 inches
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.969 inches Meter Body Diameter Behind Mounting Flange: 3.969 inches Background Color:
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.969 inches Meter Body Diameter Behind Mounting Flange: 3.969 inches Background Color: White single indicator single range
Mounting Arrangement Style: Four hole/stud rectangular/square Sensitivity Rating: 50.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -1.0/+1.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.969 inches Meter Body Diameter Behind Mounting Flange: 3.969 inches Background Color: White single indicator single range Pointer Color:

4 threaded stud

**Mounting Facility Type And Quantity:** 

## NSN 6625-00-538-9852

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+150.0 amperes, dc single indicator single range
Mounting Stud Diameter:
0.250 inches
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0