

View Online at <https://aerobasegroup.com/nsn/6625-00-538-9852>

Circuit Current For Which Designed:

Dc

Overall Length:

4.719 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches

Overall Height:

4.250 inches

Overall Width:

4.250 inches

Scale Division Quantity:

75 single indicator single range

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Mtg hdw 4; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.969 inches

Meter Body Diameter Behind Mounting Flange:

3.969 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+150.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.250 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0