

View Online at <https://aerobasegroup.com/nsn/6625-00-539-8007>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

1.382 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches

Overall Height:

1.766 inches

Overall Width:

1.766 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

15 single indicator single range

Environmental Protection:

Dust resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0/+5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.843 inches

Meter Body Diameter Behind Mounting Flange:

1.497 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+15.0 amperes, ac single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0