

View Online at <https://aerobasegroup.com/nsn/6625-00-539-8095>

Circuit Current For Which Designed:

Ac

Overall Length:

2.850 inches

Mounting Hole Diameter:

0.151 inches

Scale Division Quantity:

40 single indicator single range

Overall Diameter:

4.620 inches

Mounting Bolt Circle Diameter:

4.120 inches

Furnished Items And Quantity:

Nut 10; washer 10

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.000 inches

Meter Body Diameter Behind Mounting Flange:

3.500 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

6 screw and 6 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 800.0 pulse per sec single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Plus sign over positive terminal; sealed do not open on back of meter

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0