

View Online at <https://aerobasegroup.com/nsn/6625-00-539-8243>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.630 inches

**Mounting Hole Diameter:**

0.125 inches

**Scale Division Quantity:**

50 single indicator all ranges

**Frequency Rating:**

60.0 hertz

**Overall Diameter:**

2.695 inches

**Environmental Protection:**

Hermetic

**Mounting Bolt Circle Diameter:**

2.440 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Frequency Response Range:**

+30.000/+400.000 hertz

**Sensitivity Rating:**

500.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-4.0/+4.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.600 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Linear single indicator all ranges

**Measurement Range:**

+0.0/+500.0 milliamperes, ac single indicator 2nd range

**Scale Selection Method:**

Terminal

**Features Provided:**

Rectifier circuit

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 solder stud

**Phase:**

Single

**Special Features:**

2 to 4 ohms resistance

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Meets jan-i-6 requirements

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0