

View Online at <https://aerobasegroup.com/nsn/6625-00-539-8243>

Circuit Current For Which Designed:

Ac

Overall Length:

2.630 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

50 single indicator all ranges

Frequency Rating:

60.0 hertz

Overall Diameter:

2.695 inches

Environmental Protection:

Hermetic

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+30.000/+400.000 hertz

Sensitivity Rating:

500.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-4.0/+4.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.600 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+500.0 milliamperes, ac single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Rectifier circuit

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder stud

Phase:

Single

Special Features:

2 to 4 ohms resistance

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets jan-i-6 requirements

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0