NSN 6625-00-539-8354

Ammeter - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/6625-00-539-8354

Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
10 single indicator single range
Frequency Rating:
60.0 hertz
Overall Diameter:
2.695 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 7; seal 1; lockwasher 5
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+25.000/+30.000 hertz
Sensitivity Rating:
0.5 volts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches

Movement Type:Moving iron vane

NSN 6625-00-539-8354

Ammeter - Page 2 of 3



Background Color:	
White single indicator single range	
Pointer Color:	
Black single indicator single range	
Power Source:	
External	
Mounting Facility Type And Quantity:	
3 screw and 3 unthreaded hole	
Scale Graduation Type:	
Linear single indicator single range	
Measurement Range:	
+0.0/+1.0 amperes, ac single indicator single range	
Scale Selection Method:	
Terminal	
Features Provided:	
Magnetic shield and zero adjuster	
Movement Suspension Method:	
Jewel pivot base	
Circuit Attachment Method And Quantity:	
2 threaded stud	
Special Features:	
Ruggiedized	
Material:	
Steel	
Nuclear Hardness Critical Feature:	
Nonhardened	
Surface Treatment:	
Paint	
Special Test Features:	
Complies with mil-m-10304	
Style Designator:	
Round flush mtg	
Test Data Document:	
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data:	
81349-mil-m-10304/8 government specification	
Fsc Application Data:	
Test set, elect. Equip.	
Shelf Life:	
N/a	
Unit Of Measure:	

.

Demilitarization:

NSN 6625-00-539-8354

Ammeter - Page 3 of 3



Fiig:

A310a0