# NSN 6625-00-539-8539

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-539-8539

## **Overall Length:**

16.000 inches

## **Overall Height:**

24.000 inches

#### **Overall Width:**

13.000 inches

## Current Type:

Ac

## **Frequency Rating:**

60.0 hertz

## Accessory Components And Quantity:

2 adapters, binding posts, 1 cord, power, 1 filter, light, 1 lead, test, 1 manual, instruction, 2 probes, 10x attenuation

## Voltage Rating:

Between 105.0 volts and 125.0 volts

## Beam Quantity:

1

#### **Mounting Method:**

Table

#### Screen Size:

5 in.

## Sweep Circuits:

Included

#### **Generator Driven Feature:**

Not included

## Trigger Sweep Voltage Amplitude Rating:

Between 0.5 volts and 100.0 volts

## Trigger Sweep Polarity Switch:

Included

## Expanded Sweep:

Not provided

## **Amplifier Deflection Sensitivity Provision:**

Provided

## Vertical Deflection Sensitivity Voltage Rating:

0.05 volts peak to peak per inch and 50.0 microvolts peak to peak per inch

## Horizontal Deflection Sensitivity Voltage Rating:

0.2 volts any acceptable megahertz

## Input Intensity Modulation Feature:

Not provided

## Plate Direct Connection Deflection Sensitivity Provision:

Provided

# Direct Connection Vertical Deflection Sensitivity Voltage Rating:

11.0 volts cw megahertz and 13.0 volts peak megahertz

# NSN 6625-00-539-8539

Oscilloscope - Page 2 of 2



## **Direct Connection Horizontal Deflection Sensitivity Voltage Rating:**

27.0 volts peak to peak per centimeter and 29.0 volts peak to peak per centimeter

## Frequency Response Rating:

Provided

## Amplifier Input Impedance Rating Provision:

Provided

## X-axis Input Impedance Rating:

1.0 megohms

## Y-axis Input Impedance Rating:

1.0 megohms

## Z-axis Input Impedance Rating:

1.0 megohms

## Trace Storage Tube:

Not included

#### **Camera Recording Device Accommodation:**

Not provided

## Phase:

Single

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

T320-g