NSN 6625-00-539-8539

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-539-8539

Overall Length:
16.000 inches
Overall Height:
24.000 inches
Overall Width:
13.000 inches
Current Type:
Ac
Frequency Rating:
60.0 hertz
Accessory Components And Quantity:
2 adapters, binding posts, 1 cord, power, 1 filter, light, 1 lead, test, 1 manual, instruction, 2 probes, 10x attenuation
Voltage Rating:
Between 105.0 volts and 125.0 volts
Beam Quantity:
1
Mounting Method:
Table
Screen Size:
5 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Trigger Sweep Voltage Amplitude Rating:
Between 0.5 volts and 100.0 volts
Trigger Sweep Polarity Switch:
Included
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
0.05 volts peak to peak per inch and 50.0 microvolts peak to peak per inch
Horizontal Deflection Sensitivity Voltage Rating:
0.2 volts any acceptable megahertz
Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Provided

11.0 volts cw megahertz and 13.0 volts peak megahertz

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

NSN 6625-00-539-8539

Oscilloscope - Page 2 of 2

Demilitarization:

No **Fiig:** T320-g



Direct Connection Horizontal Deflection Sensitivity Voltage Rating: 27.0 volts peak to peak per centimeter and 29.0 volts peak to peak per centimeter **Frequency Response Rating:** Provided **Amplifier Input Impedance Rating Provision:** Provided X-axis Input Impedance Rating: 1.0 megohms Y-axis Input Impedance Rating: 1.0 megohms **Z-axis Input Impedance Rating:** 1.0 megohms **Trace Storage Tube:** Not included **Camera Recording Device Accommodation:** Not provided Phase: Single Shelf Life: N/a **Unit Of Measure:**