

View Online at <https://aerobasegroup.com/nsn/6625-00-539-8546>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

3.350 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.875 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.875 inches

**Overall Height:**

2.380 inches

**Overall Width:**

2.380 inches

**Mounting Hole Diameter:**

0.218 inches

**Scale Division Quantity:**

24 single indicator single range

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Term. Hdw 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

5.0 milliamperes

**Dial Scale Marking Color:**

Yellow, fluorescent single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

2.125 inches

**Meter Body Diameter Behind Mounting Flange:**

2.078 inches

**Movement Type:**

Moving iron vane

**Background Color:**

Black single indicator single range

**Pointer Color:**

Yellow, fluorescent single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+115.0 amperes, ac single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Phase:**

Single

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Special Test Features:**

Conforms to mil-i-8374 and ms335480

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Used w/external current transformer

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0