NSN 6625-00-539-8733

Ammeter - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/6625-00-539-8733

| Circuit Current For Which Designed: |
|---|
| Dc |
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.500 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Overall Diameter: |
| 3.500 inches |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud triangular |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.170 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.750 inches |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 3 flange |
| Measurement Range: |
| +0.0/+125.0 amperes, dc single indicator single range |
| Circuit Attachment Method And Quantity: |
| 2 binding post |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 6625-00-539-8733

Ammeter - Page 2 of 2



Fiig:

A310a0