NSN 6625-00-539-8844

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-539-8844

Overall Length:					
18.500 inches					
Overall Height:					
10.500 inches					
Overall Width:					
12.500 inches					
Current Type:					
Ac					
Frequency Rating:					
Between 0.05 kilohertz and 1.60 kilohertz					
Case Material:					
Aluminum					
Case Surface Treatment:					
Enameled					
Frequency Range Rating:					
+0.075/+40.000 megahertz					
Internal Battery Accommodation:					
Not included					
Output Impedance Rating:					
1000.0 ohms					
Voltage Rating:					
Between 105.0 volts and 125.0 volts					
Frequency Band Quantity:					
6					
Modulation Type:					
Am					
Calibration Accuracy Rating:					
Porm 1 pct accuracy of calibration					
Crystal Controlled Feature:					
Provided					
Calibrated Signal Output Range:					
1 uv to 1v					
Modulator Location:					
Internal					
Modulated Frequency Rating:					
Modulated Frequency Rating: Between 0.4 kilohertz and 1.0 kilohertz					
Between 0.4 kilohertz and 1.0 kilohertz					
Between 0.4 kilohertz and 1.0 kilohertz Modulation Degree:					
Between 0.4 kilohertz and 1.0 kilohertz Modulation Degree: 50.0 percent					
Between 0.4 kilohertz and 1.0 kilohertz Modulation Degree: 50.0 percent Phase:					

No. Ts-413 b/u type

NSN 6625-00-539-8844

Signal Generator - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-j