## NSN 6625-00-539-8844

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-539-8844

Overall Length:
18.500 inches
Overall Height:
10.500 inches
Overall Width:
12.500 inches
Current Type:
Ac
Frequency Rating:
Between 0.05 kilohertz and 1.60 kilohertz
Case Material:
Aluminum
Case Surface Treatment:
Enameled
Frequency Range Rating:
+0.075/+40.000 megahertz
Internal Battery Accommodation:
Not included
Output Impedance Rating:
1000.0 ohms
Voltage Rating:
Between 105.0 volts and 125.0 volts
Frequency Band Quantity:
6
Modulation Type:
Am
Calibration Accuracy Rating:
Porm 1 pct accuracy of calibration
Crystal Controlled Feature:
Provided
Calibrated Signal Output Range:
1 uv to 1v
Modulator Location:
Internal
Modulated Frequency Rating:
Modulated Frequency Rating:  Between 0.4 kilohertz and 1.0 kilohertz
Between 0.4 kilohertz and 1.0 kilohertz
Between 0.4 kilohertz and 1.0 kilohertz  Modulation Degree:
Between 0.4 kilohertz and 1.0 kilohertz  Modulation Degree:  50.0 percent
Between 0.4 kilohertz and 1.0 kilohertz  Modulation Degree:  50.0 percent  Phase:

No. Ts-413 b/u type

## NSN 6625-00-539-8844

Signal Generator - Page 2 of 2



_					
CI	~~	14	I i	ife:	
J.	16			HE.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T320-j