NSN 6625-00-539-9030

Radio Test Set - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-539-9030

Width:

20.000 inches

Length:

18.300 inches

Ac Voltage Rating:

126.500 volts

Frequency Rating:

50.000 hertz

Major Components:

Badapter, test; attenuator, fixed, cable assembly, power electrical; case, test set; connector; cord; coupler-detector, radio frequency; dummy load, electrical; generator, sweep; network, impedance matching; prod test

Accessory Component Quantity:

1 and 1 and 9 and 1 and 1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jcens and jcens

Accessory Identifying Number:

Mx-1982/trm-3 type no. And cn-374/trm-3 type no. And cx-3277/u type no. And cy-1941/trm-3 type no. And ug-491a/u type no. And cg-409a/u type no. And cu-506/trm-3 type no. And da-138/trm-3 type no. And sg-24/trm-3 type no. And mx-1983/trm-3 type no. And mx1981/trm-3 type no.

Internal Battery Accommodation:

Not included

Material And Location:

Aluminum carrying case

Inclosure Feature:

Single item w/carrying case

Test Type For Which Designed:

Alignment of radio frequency circuits

Operating Test Capability:

Sweep generator, range 15 to 400 mc, output oil to 100, 000 uv, internal modulation 400 cycles

Phase:

Single

Functional Classification:

Aa-6.3

Functional Description:

Designed to provide modulated and continuous wave signals at low to very low power levels. Used in testing, calibrating, aligning and setting gain adjustment in intermediate stages of radio equipment. Is intended for use at intermediate and depot levels of maintenance

Height:

21.000 inches

Reference Data And Literature:

Handbook, operating instructions: navar-16-30 trm-3-501; handbook, service instructions: navaer-16-30 trm-3-502; handbook, overhaul instructions: navaer-16-30 trm-3-503; illustrated parts breakdown: navaer-16-30 trm-3-504

Type/model Designation:

An/trm-3

Shelf Life:

. . .

NSN 6625-00-539-9030

Radio Test Set - Page 2 of 2



Demilitarization:

No

Fiig:

T228-a