

View Online at <https://aerobasegroup.com/nsn/6625-00-539-9279>

Overall Length:

14.750 inches

Overall Height:

15.000 inches

Overall Width:

17.125 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 450.0 hertz

Accessory Components And Quantity:

11 adapters, 2 rf cables, 2 test prods

Voltage Rating:

Between 105.0 volts and 125.0 volts

Beam Quantity:

1

Mounting Method:

Portable

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Frequency Range:

+8.000/+600000.000 hertz

Single Trigger Sweep Duration:

Between 0.00125 milliseconds and 125.00000 milliseconds

Trigger Sweep Polarity Switch:

Not included

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

35.0 millivolts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

4.0 volts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0005 kilohertz and 700.0000 kilohertz

Y-axis Frequency Response Rating:

Between 0.0000015 megahertz and 10.0000000 megahertz

Z-axis Frequency Response Rating:

Between 0.00005 megahertz and 10.00000 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

5.6 megohms

Y-axis Input Impedance Rating:

300.0 kilohms

Z-axis Input Impedance Rating:

56.0 kilohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g